

<b>Technical Specifications</b>		
	<b>SP2600</b>	<b>SP4600</b>
<b>Output Power</b>		
<i>Continuous Average Power</i>		
<i>RMS, 1kHz, 1.0% THD+N</i>		
@ 2Ω	2x 1950 W	2x 3450 W
@ 4Ω	2x 1300 W	2x 2300 W
@ 8Ω	2x750 W	2x 1300 W
Bridge @ 4Ω	3900 W	6900 W
Bridge @ 8Ω	2600 W	4600 W
<i>Pink Noise 12dB Crest Factor</i>		
@ 2Ω	2x 2600 W	2x 4600 W
@ 4Ω	2x 1580 W	2x 2700 W
<b>Frequency Response</b>		
Power Bandwidth ±0.25dB	20Hz-20kHz	20Hz-20kHz
<b>Phase Response</b>		
@ 1 watt 20Hz-20kHz	±15 deg	±15 deg
<b>Total Harmonic Distortion</b>		
20Hz-20kHz	<0.1%	<0.1%
<b>Intermodulation Distortion</b>		
SMPTE	<0.05%	<0.05%
<b>Crosstalk</b>		
20Hz-20kHz	>75 dB	>75 dB
<b>Slew Rate</b>		
	>65 V/μs	>65 V/μs
<b>Damping Factor</b>		
20Hz-1kHz	>800	>800
<b>Voltage Gain</b>		
	33.1 dB	33.1 dB
<b>Sensitivity</b>		
Rated Power @ 4Ω	1.6 V	2.1 V
<b>Signal-to-Noise Ratio</b>		
No weighting	105 dB	107 dB
<b>Required AC Mains</b>		
230 V - 50 Hz (idle)	0.5A	0.5A
@ 4Ω (1/8 rated power)	7 A	13 A
<b>Dimensions</b>		
W x H x D (mm)	483x89x460	483x89x460
W x H x D (inches)	19x3.5x18.1	19x3.5x18.1
<b>Weight</b>		
Shipping	14Kg-30.4Lbs	15Kg-32.6Lbs
Net	13Kg-28.3Lbs	14Kg-30.4Lbs