



## Bassline

### Single cabinet line array

Like the Dreamline, the Bassline is a slender 2,2 meter high line-array assembly, weighing only 110 kg including the pragmatic Angle Adapter™ rigging hardware. This conveniently allows single point suspension at almost any theatre batten lift. Horizontal aiming in steps of 5 degrees allow optimal audience coverage.

The Bassline is a valuable supplement for or demanding and otherwise loud events. Flying one or two Basslines next to a Dreamline results in far better controlled low-mid beaming, with far less room reflection and a powerful "punch" often missed in other flying bass.

#### Acoustical specifications

|                                |   |
|--------------------------------|---|
| Drivers                        | 6 x 12" High power, high efficiency ND magnets          |
| Freq. response                 | 60Hz-250Hz  |
| Max. peak SPL @1m <sup>1</sup> | 144dB   |
| Coverage angle                 | Omni (Horizontal) 120° - 180° curvilinear<br>(Vertical) |

#### Electrical specifications

|                    |   |
|--------------------|---|
| Amplifier(s)       | CCD™ technology   |
| Output             | 3x2500W* sine LF (DALC limited)   |
| Low pass 4th order | -250Hz <sup>2</sup>   |
| Filter hipass      | 60Hz, 4th order   |
| Input impedance    | 20 kOhms balanced, 10 kOhms unbalanced  |
| Output impedance   | Hard-wired to input   |
| Main voltage       | 230V (other on request)   |
| Mains frequency    | 50 / 60 Hz  |
| Idle               | < 50VA  |
| Full load          | < 3000VA. DALC limited Ref.<br>to continuous pink noise signal (12 dB crest<br>factor within the specified range) |
| Protection         | D.A.L.C. (Dual Audio Logic Control)   |

<sup>1</sup> Peak level at 1M under half space conditions using pink noise with crest factor 4 (12dB)

<sup>2</sup> Depending on combination of Dreamline version and venue

\* Specified at 4 Ω

#### Additional descriptive data

|                      |   |
|----------------------|---|
| Cabinet construction | Cross grain laminated multiplex   |
| Finish               | Nano-armor™ coating   |
| Weight               | 110 kg  |
| Size WxHxD (mm)      | 415 x 2205 x 840  |
| Rigging points       | Integrated single liftpoint levelbar, angle adapter<br>with trussclamp (optional) |
| Audio connectors     | IEC XLR-3 in/out  |
| Main connectors      | Powercon in, powercon out   |
| Max. operating temp. | -10 to 40 C ambient   |

